



REDLINE 12-80 V DC

Červené světlo pro označení

EEW2015R
ECCO Red line 12-80 V

- 360 ° výstražná indikace
- Extrémně odolné proti nárazům a vibracím
- Polykarbonátová čočka
- Hliníkové pouzdro



POPIS PRODUKTU

SPECIFIKACE

Barva	Čirá
Barva světla	Červená
Baterie	Ne
EMC	R10
Hmotnost	0,27 kg
Materiál	Hliník
Napětí	12-80V
Počet LED diod	3 ks
Provozní teplota max.	50 °C
Provozní teplota min.	-30 °C
Šířka	62 mm
Šířka základny	74 mm
Světelný tok	86 lm
Typ zdroje	Červená LED
Výška	65 mm

REVISIONS	
1	INITIAL DESIGN
2	DESIGN CHANGES
3	REVISED
4	REVISED

SPECIFICATIONS

- CERTIFICATION: ENEC, ENEC-C, RoHS
- Note: Initial construction, dimensions and materials list are for reference only. The product is subject to change without notice. Confirmation is required for any deviations upon the final product model configuration.
- RAWMATERIALS: 6061-T6
- EFFECTIVE LUMEN: 65 Lumens
- LUMENANCE: 12 lux
- BEAM SPREAD: 140° (C0-140)
- EFFICACY: 116.5 lm/W
- OPERATING TEMPERATURE: 1800K
- VOLTAGE (NOMINAL): 12V DC
- VOLTAGE RANGE: 9V to 15V DC
- CURRENT (PEAK): 0.55A (at 12VDC NOMINAL)
- POWER (MAXIMUM): 6.6W (at 12VDC NOMINAL)
- TEMPERATURE RANGE: 20° to 125° (T2) (20° to 50° C)
- CONNECTION: 2 - 18 AWG WIRE CABLE
- MOUNTING: BRACKET MOUNT
- MOUNTING MATERIAL: ALUMINUM
- LINK MATERIAL: POLYCARBONATE
- PRODUCT WEIGHT: 0.183 (0.37 lb)

DISCLAIMER
DIMENSIONAL, ILLUSTRATIONAL, SPECIFICATION AND CERTIFICATION CONTAINED IN THE DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. EDDO ENGINEERING DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THE PRODUCT.

MOUNTING DISCLAIMER
MOUNTING MEASUREMENTS FOR REFERENCE ONLY. MEASURE BEFORE DRILLING.

NOTES:
1. ENEC COMPLIANT
2. DIMENSIONS IN MILLIMETERS FOR REFERENCE ONLY

DESIGNER	DATE	APPROVED	DATE
DESIGNED BY	DATE	DESIGNED BY	DATE
DESIGNED BY	DATE	DESIGNED BY	DATE
DESIGNED BY	DATE	DESIGNED BY	DATE
DESIGNED BY	DATE	DESIGNED BY	DATE

WORKLAMP LED LINE 12-0V RED

ECCO ENGINEERING