



SNÍMAČE TEPLOTY TC10-F

Série TC10-F

TC10F-14369122

Snímač teploty Typ K -40-1200°C 250x12mm DN40
form 2F



- Termočlánky K, J, E, N, T
- Teplota -40 až 1200°C
- Připojení příruba
- Média voda, plyny, oleje
- ATEX, IECEx, SIL2, GOST

POPIS PRODUKTU

SPECIFIKACE

Insertion length	250 mm
Inside diameter	7 mm
Materiál kontaktní části	Nerez ocel 316Ti
Materiál těla	Hliník
Neck length	0,065 m
Plug diameter	12 mm
Provozní teplota max.	1200 °C
Provozní teplota min.	-40 °C
Temperature resistance housing from	-40 °C
Temperature resistance housing to	80 °C
Tlaková odolnost	16 bar
Třída krytí	IP65

Connection head

■ European designs per EN 50446 / DIN 43735



Model	Material	Cable entry thread size	Ingress protection (max. 1)	Cap	Surface	Connection to neck tube
BS	Aluminum	M20 x 1.5 or 1/2 NPT ¹⁾	IP65, IP68	Flat cap with 2 screws	Blue, lacquered ¹⁾	M24 x 1.5, 1/2 NPT
BSZ	Aluminum	M20 x 1.5 or 1/2 NPT ¹⁾	IP65, IP68	Spherical hinged cover with cylinder head screw	Blue, lacquered ¹⁾	M24 x 1.5, 1/2 NPT
BSZ-H	Aluminum	M20 x 1.5 or 1/2 NPT ¹⁾	IP65, IP68	Raised hinged cover with cylinder head screw	Blue, lacquered ¹⁾	M24 x 1.5, 1/2 NPT
BSZ-H (2x cable outlet)	Aluminum	2 x M20 x 1.5 or 2 x 1/2 NPT ¹⁾	IP65, IP68	Raised hinged cover with cylinder head screw	Blue, lacquered ¹⁾	M24 x 1.5, 1/2 NPT
BSZ-H (2x cable outlet) ¹⁾	Aluminum	M20 x 1.5 or 1/2 NPT ¹⁾	IP65	Raised hinged cover with cylinder head screw	Blue, lacquered ¹⁾	M24 x 1.5, 1/2 NPT
BSS	Aluminum	M20 x 1.5 or 1/2 NPT ¹⁾	IP65	Spherical hinged cover with clamping lever	Blue, lacquered ¹⁾	M24 x 1.5, 1/2 NPT
BSS-H	Aluminum	M20 x 1.5 or 1/2 NPT ¹⁾	IP65	Raised hinged cover with clamping lever	Blue, lacquered ¹⁾	M24 x 1.5, 1/2 NPT
BVS	Stainless steel	M20 x 1.5 ¹⁾	IP65	Precision-cut screw-on lid	Blank, electropolished	M24 x 1.5
BSZ-K	Plastic	M20 x 1.5 or 1/2 NPT ¹⁾	IP65	Spherical hinged cover with cylinder head screw	Black	M24 x 1.5
BSZ-HK	Plastic	M20 x 1.5 or 1/2 NPT ¹⁾	IP65	Raised hinged cover with cylinder head screw	Black	M24 x 1.5

Model	Explosion protection					
	without	Ex I (gas) Zone 0, 1, 2	Ex I (dust) Zone 20, 21, 22	Ex II (gas) Zone 2	Ex II (dust) Zone 22	
BS	x	x	-	-	-	
BSZ	x	x	x	x	x	
BSZ-H	x	x	x	x	x	
BSZ-H (2x cable outlet)	x	x	x	x	x	
BSZ-H (2x cable outlet) ¹⁾	x	x	-	-	-	
BSS	x	x	-	-	-	
BSS-H	x	x	-	-	-	
BVS	x	x	-	-	-	
BSZ-K	x	x	-	-	-	
BSZ-HK	x	x	-	-	-	

Cable entry



The pictures show examples of connection heads.

Cable entry	Cable entry thread size
Standard cable entry ¹⁾	M20 x 1.5 or 1/2 NPT
Plastic cable gland (cable Ø 6 ... 10 mm) ¹⁾	M20 x 1.5 or 1/2 NPT
Nickel-plated brass cable gland (cable Ø 6 ... 12 mm)	M20 x 1.5 or 1/2 NPT
Stainless steel cable gland (cable Ø 7 ... 12 mm)	M20 x 1.5 or 1/2 NPT
Plain threaded	M20 x 1.5 or 1/2 NPT
2 x M20 x 1.5 ¹⁾	2 x M20 x 1.5
Junction box M12 x 1 (4-pin) ¹⁾	M20 x 1.5
Sealing plugs for transport	M20 x 1.5 or 1/2 NPT

Electrical connection






Protection tube designs in accordance with DIN 43772				
Protection tube	Material	Protection tube Ø	Suitable for measuring insert Ø	Connection to head
Straight, form 2F DIN 43772	Stainless steel 1.4571	9 x 1 mm	6 mm	M24 x 1.5 (rotatable threaded connection, male nut)
		11 x 2 mm	8 mm	
		12 x 2.5 mm	8 mm with sleeve Ø 8 mm / 8 mm	
Tapered, form 3F DIN 43772	Stainless steel 1.4571	12 x 2.5 mm, tapered to 9 mm	6 mm	M24 x 1.5 (rotatable threaded connection, male nut)
		12 x 2.5 mm, tapered to 9 mm	6 mm	

Protection tube designs in line with DIN 43772, weld-on solid tip				
Protection tube	Material	Protection tube Ø	Suitable for measuring insert Ø	Connection to head
Tapered, weld-on solid tip, in line with DIN 43772, non-standard design	Stainless steel 1.4571	9 x 1 mm, tapered to 6 mm 11 x 2 mm, tapered to 8 mm 12 x 2.5 mm, tapered to 8 mm	6 mm	M24 x 1.5 (rotatable threaded connection, male nut)

Protection tube designs in line with DIN 43772, welded parts: special material, gilder flange: stainless steel				
Protection tube	Material	Protection tube Ø	Suitable for measuring insert Ø	Connection to head
Straight, in line with form 2F DIN 43772, non-standard design	2.450 (Aluminum) / stainless steel 2.4519 (Inconel C717) / stainless steel 2.4512 (Inconel C6) / stainless steel 3.7026 (Titan Grade 2) / stainless steel	13.7 x 2.2 mm	6 mm with sleeve Ø 8 mm / 8 mm	M24 x 1.5 (rotatable threaded connection, male nut)
		13.7 x 2.2 mm	8 mm	
		13.7 x 2.2 mm	8 mm	

Protection tube designs in line with DIN 43772, tantalum cover with tantalum flange disc, carrier protection tube: stainless steel				
Protection tube	Material	Protection tube Ø	Suitable for measuring insert Ø	Connection to head
Straight, in line with form 2F DIN 43772, non-standard design	Tantalum / stainless steel	11 x 2 mm, tantalum cover 12 x 0.4 mm	6 mm	M24 x 1.5 (rotatable threaded connection, male nut)
		15 x 3 mm, tantalum cover 16 x 0.4 mm	8 mm with sleeve Ø 8 mm / 8 mm	
Tapered, in line with form 3F DIN 43772, non-standard design	Tantalum / stainless steel	12 x 2.5 mm, tantalum cover 13 x 0.4 mm	6 mm	M24 x 1.5 (rotatable threaded connection, male nut)
		12 x 2.5 mm, tantalum cover 13 x 0.4 mm	6 mm	



- Legend
- 1) Connection head
 - 2) Neck tube
 - 3) Flange
 - 4) Measuring insert (TC10-A)
 - 5) Tantalum block/separator (optional)
 - 6) Transmitter (optional)
 - 7) Protection tube
 - 8) Flange disc from special material
 - 9) Tantalum cover
- L1 Overall length of protection tube
L2 Measuring insert length
L3 Protection tube insertion length, in accordance with DIN 43772
L4 Protection tube diameter
L5 Outer diameter of tantalum cover
L6 Neck length
L7 Neck tube length