



# TERMOČLÁNKY TC47-AB

## Série TC47-AB

TC47-AB  
Termočlánek

- Teplota -40°C až 750°C
- K, J, K, T
- Tělo nerez



### POPIS PRODUKTU

### SPECIFIKACE

Provozní teplota max.	750 °C
-----------------------	--------

Provozní teplota min.	-40 °C
-----------------------	--------

<b>Adjustable bayonet</b> <ul style="list-style-type: none"> <li>Spring up to 200 mm or 8" of adjustability</li> <li>Armour full length of adjustability</li> </ul>	<b>Lead wire</b> <ul style="list-style-type: none"> <li>Fibreglass / fibreglass</li> <li>PTFE / PTFE</li> <li>PVC / PVC</li> <li>Kapton / Kapton</li> <li>Others on request</li> </ul>												
<b>Insulation</b> <ul style="list-style-type: none"> <li>Grounded (unisolated)</li> <li>Ungrounded (isolated)</li> </ul>	<b>Lead wire covering</b> <ul style="list-style-type: none"> <li>None</li> <li>Stainless steel overbraid (no tracer)</li> <li>Stainless steel overbraid (with tracer)</li> <li>Tin copper overbraid</li> <li>Interlocking flexible armour</li> </ul>												
<b>Tip diameter (Ø)</b> <ul style="list-style-type: none"> <li>3/16"</li> <li>1/4"</li> <li>3/8"</li> <li>4 mm</li> <li>6 mm</li> <li>8 mm</li> <li>10 mm</li> <li>Others on request</li> </ul>	<b>Termination at lead end</b> <ul style="list-style-type: none"> <li>Bare ends</li> <li>Standard thermo plug 2-pin (male)</li> <li>Miniature thermo plug 2-pin (male)</li> <li>Standard plug with cable clamp (male)</li> <li>Miniature plug with cable clamp (male)</li> <li>Lemosia plug size 15 (male)</li> <li>Lemosia plug size 25 (male)</li> <li>Screw-in-plug, Binder (male)</li> <li>Others on request</li> </ul>												
<b>Probe length</b> <ul style="list-style-type: none"> <li>Standard</li> <li>Others on request</li> </ul>	<b>Bayonet cap</b> <table border="1"> <thead> <tr> <th>Id Ø</th> <th>Fits bayonet adapter</th> </tr> </thead> <tbody> <tr> <td>Single slot 11.4 mm (7/16")</td> <td>11 mm O.D.</td> </tr> <tr> <td>Double slot 11.4 mm (7/16")</td> <td>11 mm O.D.</td> </tr> <tr> <td>Double slot 12.2 mm (3/16")</td> <td>12 mm O.D.</td> </tr> <tr> <td>Double slot 14.2 mm (9/16")</td> <td>12 mm O.D.</td> </tr> <tr> <td>Double slot 15.2 mm (19/32")</td> <td>15 mm O.D.</td> </tr> </tbody> </table>	Id Ø	Fits bayonet adapter	Single slot 11.4 mm (7/16")	11 mm O.D.	Double slot 11.4 mm (7/16")	11 mm O.D.	Double slot 12.2 mm (3/16")	12 mm O.D.	Double slot 14.2 mm (9/16")	12 mm O.D.	Double slot 15.2 mm (19/32")	15 mm O.D.
Id Ø	Fits bayonet adapter												
Single slot 11.4 mm (7/16")	11 mm O.D.												
Double slot 11.4 mm (7/16")	11 mm O.D.												
Double slot 12.2 mm (3/16")	12 mm O.D.												
Double slot 14.2 mm (9/16")	12 mm O.D.												
Double slot 15.2 mm (19/32")	15 mm O.D.												
<b>Lead length</b> <ul style="list-style-type: none"> <li>500 mm</li> <li>1000 mm</li> <li>1500 mm</li> <li>2000 mm</li> <li>2500 mm</li> <li>Others on request</li> </ul>	<b>Calibration type</b> <ul style="list-style-type: none"> <li>J ANSI MC96.1 red Ø white Ø</li> <li>K ANSI MC96.1 red Ø yellow Ø</li> <li>T ANSI MC96.1 red Ø blue Ø</li> <li>J IEC 584-3 white Ø black Ø</li> <li>K IEC 584-3 white Ø green Ø</li> <li>T IEC 584-3 white Ø brown Ø</li> <li>J DIN 43714 blue Ø red Ø</li> <li>K DIN 43714 green Ø red Ø</li> <li>T DIN 43714 brown Ø red Ø</li> <li>Others on request</li> </ul>												