



# TERMOČLÁNKY TC47-MT

Série TC47-MT

TC47-MT  
Termočlánek

- Teplota -40°C až 750°C
- K, J, K, T
- Tělo nerez








## POPIS PRODUKTU

## SPECIFIKACE

Provozní teplota max. 750 °C

Provozní teplota min. -40 °C

<b>Manifold block</b> <ul style="list-style-type: none"><li>■ Stainless steel</li><li>■ Others on request</li></ul>		<b>Lead wire covering</b> <ul style="list-style-type: none"><li>■ None</li><li>■ Stainless steel overbraid (no tracer)</li><li>■ Stainless steel overbraid (with tracer)</li><li>■ Tin copper overbraid</li><li>■ Interlocking flexible armour</li></ul>																																								
<b>Junction</b> <ul style="list-style-type: none"><li>■ Grounded (unisolated)</li><li>■ Ungrounded (isolated)</li></ul>		<b>Termination at lead end</b> <ul style="list-style-type: none"><li>■ Bare ends</li><li>■ Standard thermo plug 2-pin (male)</li><li>■ Miniature thermo plug 2-pin (male)</li></ul>																																								
<b>Tip diameter (Ø)</b> <ul style="list-style-type: none"><li>■ 4 mm</li><li>■ Others on request</li></ul>		<ul style="list-style-type: none"><li>■ Standard plug with cable clamp (male)</li><li>■ Miniature plug with cable clamp (male)</li><li>■ Lemosa plug size 15 (male)</li><li>■ Lemosa plug size 25 (male)</li><li>■ Screw-in plug, Binder (male)</li><li>■ Others on request</li></ul>																																								
<b>Tip length</b> <ul style="list-style-type: none"><li>■ 12 mm</li><li>■ 20 mm</li><li>■ 25 mm</li><li>■ Others on request</li></ul>		<b>Calibration type</b> <table><tbody><tr><td>■ J</td><td>ANSI MC96.1</td><td>red Ø</td><td>white Ø</td></tr><tr><td>■ F</td><td>ANSI MC96.1</td><td>red Ø</td><td>yellow Ø</td></tr><tr><td>■ T</td><td>ANSI MC96.1</td><td>red Ø</td><td>blue Ø</td></tr><tr><td>■ J</td><td>IEC 584-3</td><td>white Ø</td><td>black Ø</td></tr><tr><td>■ K</td><td>IEC 584-3</td><td>white Ø</td><td>green Ø</td></tr><tr><td>■ T</td><td>IEC 584-3</td><td>white Ø</td><td>brown Ø</td></tr><tr><td>■ J</td><td>DIN 43714</td><td>blue Ø</td><td>red Ø</td></tr><tr><td>■ K</td><td>DIN 43714</td><td>green Ø</td><td>red Ø</td></tr><tr><td>■ T</td><td>DIN 43714</td><td>brown Ø</td><td>red Ø</td></tr><tr><td>■ Others on request</td><td></td><td></td><td></td></tr></tbody></table>	■ J	ANSI MC96.1	red Ø	white Ø	■ F	ANSI MC96.1	red Ø	yellow Ø	■ T	ANSI MC96.1	red Ø	blue Ø	■ J	IEC 584-3	white Ø	black Ø	■ K	IEC 584-3	white Ø	green Ø	■ T	IEC 584-3	white Ø	brown Ø	■ J	DIN 43714	blue Ø	red Ø	■ K	DIN 43714	green Ø	red Ø	■ T	DIN 43714	brown Ø	red Ø	■ Others on request			
■ J	ANSI MC96.1	red Ø	white Ø																																							
■ F	ANSI MC96.1	red Ø	yellow Ø																																							
■ T	ANSI MC96.1	red Ø	blue Ø																																							
■ J	IEC 584-3	white Ø	black Ø																																							
■ K	IEC 584-3	white Ø	green Ø																																							
■ T	IEC 584-3	white Ø	brown Ø																																							
■ J	DIN 43714	blue Ø	red Ø																																							
■ K	DIN 43714	green Ø	red Ø																																							
■ T	DIN 43714	brown Ø	red Ø																																							
■ Others on request																																										
<b>Lead length</b> <ul style="list-style-type: none"><li>■ 500 mm</li><li>■ 1000 mm</li><li>■ 1500 mm</li><li>■ 2000 mm</li><li>■ 2500 mm</li><li>■ Others on request</li></ul>																																										
<b>Lead wire</b> <ul style="list-style-type: none"><li>■ Fibreglass / Fibreglass</li><li>■ PTFE / PTFE</li><li>■ PVC / PVC</li><li>■ Kapton / Kapton</li><li>■ Others on request</li></ul>																																										