



TERMOČLÁNKY TC47-NT

Série TC47-NT

TC47-NT
Termočlánek

- Teplota -40°C až 750°C
- K, J, K, T
- Tělo nerez



POPIS PRODUKTU

SPECIFIKACE

Provozní teplota max. 750 °C

Provozní teplota min. -40 °C



Nozzle bolt material <ul style="list-style-type: none">■ Stainless steel■ Brass■ Others on request	Lead wire covering <ul style="list-style-type: none">■ None■ Stainless steel overbraid (no tracer)■ Stainless steel overbraid (with tracer)■ Tin copper overbraid
Junction <ul style="list-style-type: none">■ Grounded (isolated)■ Ungrounded (isolated)	Termination at lead end <ul style="list-style-type: none">■ Bare ends■ Standard thermo plug 2-pin (male)■ Miniature thermo plug 2-pin (male)■ Standard plug with cable clamp (male)■ Miniature plug with cable clamp (male)■ Lemosa plug size 1G (male)■ Lemosa plug size 2S (male)■ Screw-in plug, Binder (male)■ Others on request
Nozzle bolt thread size <ul style="list-style-type: none">■ 1/4 x 28■ M5■ M8■ Others on request	Calibration type <ul style="list-style-type: none">■ J ANSI MC96.1 red Ø white Ø■ K ANSI MC96.1 red Ø yellow Ø■ ANSI MC96.1 red Ø black Ø■ J IEC 584-3 white Ø black Ø■ K IEC 584-3 white Ø green Ø■ T IEC 584-3 white Ø brown Ø■ J DIN 43714 blue Ø red Ø■ K DIN 43714 green Ø red Ø■ T DIN 43714 brown Ø red Ø■ Others on request
Lead length <ul style="list-style-type: none">■ 500 mm■ 1000 mm■ 1500 mm■ 2000 mm■ 2500 mm■ Others on request	
Lead wire <ul style="list-style-type: none">■ Fibreglass / Fibreglass■ PTFE / PTFE■ PVC / PVC■ Kapton / Kapton■ Others on request	