



# TERMOČLÁNKY TC47-AC

## Série TC47-AC

TC47-AC  
Termočlánek



- Teplota -40°C až 750°C
- K, J, K, T
- Tělo nerez



## POPIS PRODUKTU

## SPECIFIKACE

Provozní teplota max. 750 °C

Provozní teplota min. -40 °C

<b>Adjustable compression version</b> <ul style="list-style-type: none"> <li>■ Straight</li> <li>■ 45° bend</li> <li>■ 90° bend</li> </ul>	
<b>Junction</b> <ul style="list-style-type: none"> <li>■ Grounded (unisolated)</li> <li>■ Ungrounded (isolated)</li> </ul>	
<b>Probe diameter</b> <ul style="list-style-type: none"> <li>■ 3/16"</li> <li>■ 1/4"</li> <li>■ 3/8"</li> <li>■ 4 mm</li> <li>■ 6 mm</li> <li>■ 8 mm</li> <li>■ Others on request</li> </ul>	
<b>Probe length</b> <ul style="list-style-type: none"> <li>■ Standard: 100 mm (4")</li> <li>■ Others on request</li> </ul>	
<b>Compression fitting material</b> <ul style="list-style-type: none"> <li>■ Brass</li> <li>■ Stainless steel</li> <li>■ None</li> </ul>	
<b>Thread size</b> <ul style="list-style-type: none"> <li>■ Thread size on request</li> </ul>	
<b>Lead length</b> <ul style="list-style-type: none"> <li>■ 500 mm</li> <li>■ 1000 mm</li> <li>■ 1500 mm</li> <li>■ 2000 mm</li> <li>■ 2500 mm</li> <li>■ Others on request</li> </ul>	
<b>Lead wire</b> <ul style="list-style-type: none"> <li>■ Fibreglass / Fibreglass</li> <li>■ PTFE / PTFE</li> <li>■ PVC / PVC</li> <li>■ Kapton / Kapton</li> <li>■ Others on request</li> </ul>	
<b>Lead wire covering</b> <ul style="list-style-type: none"> <li>■ None</li> <li>■ Stainless steel overbraid (no tracer)</li> <li>■ Stainless steel overbraid (with tracer)</li> <li>■ Tin copper overbraid</li> <li>■ Interlocking flexible armour</li> </ul>	
<b>Termination at lead end</b> <ul style="list-style-type: none"> <li>■ Bare ends</li> <li>■ Standard thermo plug 2-pin (male)</li> <li>■ Miniature thermo plug 2-pin (male)</li> <li>■ Standard plug with cable clamp (male)</li> <li>■ Miniature plug with cable clamp (male)</li> <li>■ Lemosa plug size 15 (male)</li> <li>■ Lemosa plug size 25 (male)</li> <li>■ Screw-in plug, Binder (male)</li> <li>■ Others on request</li> </ul>	
<b>Calibration type</b> <ul style="list-style-type: none"> <li>■ J ANSI MC96.1 red ⊕ white ⊕</li> <li>■ K ANSI MC96.1 red ⊕ yellow ⊕</li> <li>■ T ANSI MC96.1 red ⊕ blue ⊕</li> <li>■ J IEC 584-3 white ⊕ black ⊕</li> <li>■ K IEC 584-3 white ⊕ green ⊕</li> <li>■ T IEC 584-3 white ⊕ brown ⊕</li> <li>■ J DIN 43714 blue ⊕ red ⊕</li> <li>■ K DIN 43714 green ⊕ red ⊕</li> <li>■ T DIN 43714 brown ⊕ red ⊕</li> <li>■ Others on request</li> </ul>	